



JUMP STARTER SOS BOOSTER® SOS 12/24V - 1600/800CA

APPLICATIONS



MOTOR		
Vehicle	12V	24V
Gasoline	✓	✓
Diesel	✓	

TYPE OF RECOVERY
12V vehicles: intensive
Laborious starts, recovery of a vehicle with completely flat battery
Successive jump starts, several times during the day
Difficult conditions of use*
24V vehicles: occasional
Recovery of a lightly discharged battery
Normal conditions of use



The correct use of a Ceteur Booster cannot cause any damage to the electronic of a vehicle.













Ceteur booster packs are perfectly compatible with hybrid vehicles.

* Extreme conditions of use such as frost, extreme heat...



TYPE OF VEHICLES TO BE JUMP STARTED
New or second-hand car, 4Wd and commercial vehicle (van)
New or second-hand tractor
Light civil engineering equipment
New or second hand 12V truck
24V truck in good condition
Leisure plane and boat

Diesel motors up to*:

POWER IN HP

12V							24V				
<125	150	175	250	300	350	500	100	250	500	1000	1500
											

* Petrol motors are easier to start

 Normal
 Intensive







Following the principle "who can do more can do less" our most powerful battery boosters can also be convenient for the applications covered by less powerful battery boosters with same voltage of our range.

Caution :

The circumstances/conditions when starting a vehicle depend of various parameters: vehicle's condition, engine type (petrol or diesel) and power, presence of battery in vehicle or not, temperature, frequency of use ... Those influence the jump start's facility. *Chart for your information - Manufacturer's advice.*

TECHNICAL SPECIFICATIONS

Reference	761006
Voltage	12/24V
Cranking Amps	1600/800 A
Peak Amps	4740/2370 A
Nr of batteries	2
Starting cable length	1,35 m
Starting cable diameter	35 mm ²
Type of clamps	850 A
Clamps length	215 mm
Clamps opening	54 mm
AC/DC* charger	2 A
Cable to charge DC/12V	
12V Output	16 A
Reverse polarity signal	
Internal fuse	300 A
Connector for auxiliary cables	
Net weight	20,5 kg
Dimensions (cm)	53 x 16 x 48
Gross weight	23 kg
Packing dimensions (cm)	56 x 19 x 60,5

 Yes
 No
 Option
 Upon request

STANDARD EQUIPMENT



LED CLAMPS

The blue clamp is equipped with a led (lamp) for an easier and safer use, especially in the dark.



SWITCH & BUZZER

This booster is equipped with a switch to improve security during use and a polarity reverse signal as well as flat free wheels which make it the perfect tool for workshops, depots and parking lots.